



Product Data Sheet

Manual Pallet Stacker Xilin 1000MS

ADVANTAGES:

- Forks suitable for EUR pallets
- High quality steel mast and strong steel construction ensures rigidity and durability
- Welded fork delivers low-cost solution
- High efficient pump makes the stacker easier to operate
- Ergonomic foot-, and hand controlled lifting function
- Protective mesh screen ensures safe operation
- With safety guard and brake system



SPECIFICATIONS:

Model		1000MS160	1000MS250	1000MS300
Load capacity	(Kg)	1.000	1.000	1.000
Load centre distance	c (mm)	600	600	600
Fork height, lowered	h13 (mm)	90	90	90
Height, mast lowered	h1 (mm)	2.080	1.838	2.080
Max. lift height	h3 (mm)	1.600	2.500	3.000
Height, mast extended	h4 (mm)	2.080	2.925	3.420
Overall length	l1 (mm)	1.685	1.695	1.695
Overall width	b1 (mm)	755	860	860
Fork dimensions	s/e/l (mm)	55/170/1.150	55/170/1.150	55/170/1.150
Width overall forks	b5 (mm)	550	580	580
Ground clearance, below mast, loaded	m1 (mm)	20	20	20
Aisle width for pallet 1000x1200 crossways	Ast (mm)	2.057	2.082	2.082
Aisle width for pallet 800x1200 lengthways	Ast (mm)	1.991	2.016	2.016
Turning radius	Wa (mm)	1.325	1.350	1.350
Lift speed, loaded/unloaded	mm/time	20/22	20/22	20/22
Lowering speed, loaded, unloaded	mm/s	Manual control	Manual control	Manual control
Service weight	Kg	214	292	305

